



ChemWorld.com

Worldwide Online Ordering and Consulting

GEORGIA WAREHOUSE

3939 Royal Drive, Suite 139,
Kennesaw, GA, 30144

MICHIGAN WAREHOUSE

25991 Northline Commerce Dr.
Unit 504 Taylor, MI 48180

UTAH WAREHOUSE

647 West Billinis Road, Unit 1
Salt Lake City, Utah 84119

Chemworld Cold Fog

Specialty Hydrogen Peroxide Cold Fogging Additive to Treat Interiors of Transportation Vehicles and Enclosed Spaces

Chemworld Cold Fog is a concentrated blend of oxygen bleach and biodegradable penetrants designed for use as a biostat hydrogen peroxide fogging agent. Chemworld Cold Fog reduces contaminants and eliminates odors providing fast and effective cleaning of all surfaces. Chemworld Cold Fog can be applied by cold fogging misting equipment to the interiors of vehicles, plants walls, floors, most furniture, most fabrics, and almost all non-porous and semi-porous with a vehicle or structure (as long as they are resistant to a light mist of water). Chemworld Cold Fog can also be used in non-recirculated spray-on and mop bucket applications. Add product at 100%BV to fogger. There are no odor, toxic, or contamination problems when using Chemworld Cold Fog as the only decomposition products are oxygen and water. Concentration coming out of the mister is 50,000-ppm as hydrogen peroxide bleach. When in doubt, pre-testing of surfaces is always recommended.

PRODUCT PROPERTIES:

Appearance:	Clear liquid, odor nil.
Specific Gravity:	1.02
Solubility:	Complete
Flash Point:	None
pH(100%):	5.0-6.0

USE INFORMATION:

Concentration:	100%BV
Bucket applications	2:1 dilution with water to wipe down contact areas.
Temperature:	Ambient to 120°F.
Contact Time:	>10-minutes. Remove non-compatible items from vehicle. Note: Make sure vapor is released from vehicle and contact surfaces are wiped dry prior to re-entry of any enclosed space.

PRECAUTIONS: May cause irritation to the eyes upon contact. ****AVOID CONTACT****
Prolonged contact may cause skin irritation. When handling, wear proper personal protective equipment as indicated by the accompanying OSHA material safety data sheet. If accidental contact is made immediately flush contacted area repeatedly with cool water. If irritation persists call a physician for treatment. If accidental eye contact occurs flush eyes with cool water and seek the immediate attention of a physician. Launder contaminated clothing before reuse. Wash thoroughly after handling. **FOR INDUSTRIAL & COMMERCIAL USE ONLY!**

PACKAGE: Bulk, 330, 275, 55, 30, 15, and 5-gallon pails.