



ATLANTA WAREHOUSE
3939 Royal Drive, Suite 139
Kennesaw, GA 30144

UTAH WAREHOUSE
647 West Billinis Road, Unit 1
Salt Lake City, Utah 84119

ChemWorld ALK SPRAY

Extremely Heavy-Duty, Oil Rejecting Alkaline Cleaner

ChemWorld ALK SPRAY is a concentrated blend of alkaline builders, particulate dispersants, water conditioners, demulsifiers, and low foaming detergents balanced for maximum soil penetration and removal. ChemWorld ALK SPRAY is formulated for use in all multi-stage immersion, electrolytic, and recirculating industrial wash systems. ChemWorld ALK SPRAY is suitable for use on ferrous metals, durable plastic, as well as titanium, stainless steel, copper, and other metals which are resistant to strong alkali. ChemWorld ALK SPRAY is COMPLETELY NON-FOAMING under normal use conditions, however, ChemWorld ALK SPRAY may foam if sprayed at temperatures below 100°F. ChemWorld ALK SPRAY offers excellent particle soil removal, very good oil rejection, and provides convenience and economy as a liquid cleaner. ChemWorld ALK SPRAY is suitable for automatic chemical feeding, and is very effective with specialty Thin-Film™ oil removal equipment that demands a thin, non-adulterated oil film to perform properly.

- Formulated with oil rejecting surfactants and detergents for outstanding tank life.
- Cleans all soils; including paraffins, sterates, heavy greases, mild rust, and soluble oils.
- Offers completely foam-free spray and immersion cleaning.
- One of the best spray cleaners for heavy smut, grease, and particulate.

PROPERTIES:

Appearance:	Clear amber liquid
Specific Gravity:	1.25 (Very high concentrate)
pH(1%):	>12.0
Biodegradability:	Detergents are 100% biodegradable.
Oil Rejection Capability:	>99.5%
V.O.C. Content	None

USE INFORMATION:

Concentration:	0.5-6.0%	Spray
	2.0-8.0%	Immersion
Temperature:	100-200°F	Spray
	80-200°F	Immersion

PRECAUTIONS: May cause severe burns to the skin and eyes upon contact. **AVOID CONTACT** FOR INDUSTRIAL USE ONLY! Refer to MSDS.

STANDARD PACKAGING SIZES: Bulk, 330 + 275 gal, 55 gal, 30 gal, 15 gal, and 5 gal. containers.
OPTIONAL: Private labeling. Bulk container packaging from 1 oz to 5 gallons.