



ATLANTA WAREHOUSE
3939 Royal Drive, Suite 139
Kennesaw, GA 30144

UTAH WAREHOUSE
647 West Billinis Road, Unit 1
Salt Lake City, Utah 84119

ChemWorld Defoam

High Performance Defoamer, Rust Inhibitor, and Bacteriostat

ChemWorld Defoam is a 100% active, non-silicone oil, defoamer which provides efficient defoaming with permanent effect in most applications. ChemWorld Defoam is based on highly complex organic defoaming agents that destroy foam on both the systems surface and solution. ChemWorld Defoam is especially effective on detergent/soap produced and sustained foam in Non-heated and lightly-heated spray systems. ChemWorld Defoam contains no petroleum hydrocarbons, solvents, or VOC's and will not stain aluminum, yellow, and ferrous metals.

ChemWorld Defoam finds application in controlling foam in many areas including, industrial spray washers, cooling towers, paper mill applications, effluent foam control, and paint booth treatments. ChemWorld Defoam, being a stable clear liquid, is highly suited for automatic chemical dispensing where applicable. ChemWorld Defoam is highly effective and economical by eliminating the need to slug-feed defoamer and/or rust inhibitors. ChemWorld Defoam contains 0.5%BW of extremely safe PCMX preservative-biocide, which is FDA approved for addition into hand soaps and other skin contacting detergents and washes.

PRODUCT PROPERTIES:

Appearance:	Opaque white semi-viscous liquid, odor nil.
Specific Gravity:	1.00
Flash Point:	None
pH (0.1%):	9.5 (Quickly assumes the pH of the water solution)
HMIS Rating:	1,0,0

USE INFORMATION:

Concentration:	Initial feed rate should be 1-ounce per hundred gallons of volume.
Temperature:	Effective at 60°F to 200°F.
Contact Time:	Immediate and prolonged defoaming effect.

PRECAUTIONS: May cause irritation to the eyes upon contact. Prolonged contact may cause skin irritation.

****AVOID CONTACT** FOR INDUSTRIAL & COMMERCIAL USE ONLY! Refer to MSDS!**

STANDARD PACKAGING SIZES: Bulk, 330 + 275 gal, 55 gal, 30 gal, 15 gal, and 5 gal. containers.
OPTIONAL: Private labeling. Bulk container packaging from 1 oz to 5 gallons.