



### OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 60 - Drinking Water Treatment Chemicals - Health Effects

This is the Official Listing recorded on November 13, 2017.

**Enviro Tech Chemical Service Inc**  
500 Winmoore Way  
Modesto, CA 95358

**Facility: Modesto, CA**

Chemical/ Trade Designation	Function	Max Use
<b>Ammonium Sulfate</b>		
BSLLAS	Chloramination	60 mg/L
<b>Hydrogen Peroxide</b>		
Hydrogen Peroxide 15%	Oxidant	3.5 mg/L
Hydrogen Peroxide 34%	Oxidant	3 mg/L
Hydrogen Peroxide 50%	Oxidant	2.1 mg/L
<b>Miscellaneous Treatment Chemical</b>		
Bioside HS 15% [2]	Membrane Cleaner Reverse Osmosis Antiscalant	30 mg/L
<b>Miscellaneous Water Supply Products</b>		
BSL 8000 [1]	Other	NA
BSL Pro [1]	Other	NA
Perasan A [3] [4] [5]	Membrane Cleaner	NA
REFLEX™ [3] [4] [5]	Membrane Cleaner	NA

- [1] These products are designed to be used offline to remove deposits from water tank surfaces. BSL 8000/ECO9000 and BSL Pro are used in a 10:1 ratio at a rate of 60 mg/L. The tank is rinsed to remove any residual product before returning to service.
- [2] This product is designed to be used upstream of a carbon absorption system. Use of this product shall be followed by chlorination to remove trace levels of hydrogen peroxide.
- [3] These products are designed to be used off-line and flushed out prior to using the system for drinking water, following manufacturer's use instructions.
- [4] The pH of the influent and effluent water should be monitored to ensure that all traces of the product have been removed before placing into service.
- [5] Drain and flush system until the hydrogen peroxide and peracetic acid concentrations fall below 1 ppm.

**Facility: Helena, AR**

Chemical/ Trade Designation	Function	Max Use
<b>Miscellaneous Water Supply Products [1] [2] [3]</b>		
Bioside HS 15%	Membrane Cleaner	NA
Perasan A	Membrane Cleaner	NA

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



REFLEX™

Membrane Cleaner

NA

- [1] This product is designed to be used off-line and flushed out prior to using the system for drinking water, following manufacturer's use instructions.
- [2] The pH of the influent and effluent water should be monitored to ensure that all traces of the product have been removed before placing into service.
- [3] Drain and flush system until hydrogen peroxide and peracetic acid concentrations fall below 1 ppm.