

ATLANTA WAREHOUSE 3939 Royal Drive, Suite 139 Kennesaw, GA 30144 UTAH WAREHOUSE 647 West Billinis Road, Unit 1 Salt Lake City, Utah 84119

ChemWorld 1337 SULFITE-BASED OXYGEN SCAVENGER

DESCRIPTION

ChemWorld 1337 highly concentrated acidic sulfite solution which, when added to boiler feedwater, removes dissolved oxygen. By acting as an oxygen scavenger, ChemWorld 1337 is used to control corrosion and pitting caused by the presence of dissolved oxygen.

FEATURES AND BENEFITS

- Improves boiler system reliability and longevity
- Removes corrosive oxygen from the boiler feedwater and boiler water

PRODUCT FEED AND CONTROL

ChemWorld 1337 must be mixed in a chemical feed tank using good quality condensate, softened water, or feedwater. An agitator is required to assure complete dissolution of the product. ChemWorld 1337 may be mixed with most common chemicals used for boiler treatment. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC. Neat product is low pH and can be corrosive to feedwater systems.

ChemWorld 1337 is normally controlled by a sulfite test on the boiler water. Control ranges can vary widely depending upon both makeup water characteristics and system operating conditions and will be specified by the technical representative servicing the facility.

PHYSICAL PROPERTIES

Physical properties of ChemWorld 1337 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

ChemWorld 1337 is available in a wide variety of customized containers and delivery methods.