



ATLANTA WAREHOUSE
3939 Royal Drive, Ste 224 and 226
Kennesaw, GA 30144

UTAH WAREHOUSE
647 West Billinis Road, Unit 1
Salt Lake City, Utah 84119

CHEMWORLD 906 COOLING WATER TREATMENT FOR CLOSED SYSTEMS

DESCRIPTION

CHEMWORLD 906 is an organic closed water system treatment program. The product contains a combination of phosphonate, polymer, andazole formulated to minimize corrosion and deposition. CHEMWORLD 906 is designed for calcium chloride brine closed systems.

FEATURES AND BENEFITS

- Controls corrosion
- Extends equipment life
- Non-nitrite, non-molybdate product
- Improves overall equipment efficiency
- Protects multiple metallurgies
- Effective in both hot and cold brine systems

PRODUCT FEED AND CONTROL

CHEMWORLD 906 is normally shot fed. The product is normally added directly from the shipping container. Feeders, piping, and valves should be made of steel, polyethylene, or PVC.

Treatment control ranges vary depending on system operating conditions. CHEMWORLD 906 is controlled by a phosphonate test. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions. This product should be added to a high mix area at a slow rate to allow the inhibitors to go into solution.

PHYSICAL PROPERTIES

Physical properties of CHEMWORLD 906 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

CHEMWORLD 906 is available in a wide variety of customized containers and delivery methods.