



# Classic 45 & 85 Single Head Stenner Pumps

## Adjustable Output

### BUILD AN ITEM NUMBER FOR PUMP OR TANK SYSTEM



Select **Item Number Prefix** from output chart

#### SINGLE HEAD ADJUSTABLE 25 psi (1.7 bar)

	Model	Item Number Prefix	Pump Tube Number	Gallons per Day	Liters per Day
45 SERIES	45M1	45MJL1	#1	0.2-3.0	0.8-11.4
	45M2	45MJL2	#2	0.5-10.0	1.9-37.9
	45M3	45MJL3	#3	1.1-22.0	4.2-83.3
	45M4	45MJL4	#4	1.7-35.0	6.4-132.5
	45M5	45MJL5	#5	2.5-50.0	9.5-189.3
85 SERIES	85M1	85MJL1	#1	0.3-5.0	1.1-18.9
	85M2	85MJL2	#2	0.8-17.0	3.0-64.4
	85M3	85MJL3	#3	2.0-40.0	7.6-151.4
	85M4	85MJL4	#4	3.0-60.0	11.4-227.1
	85M5	85MJL5	#5	4.3-85.0	16.3-321.8

#### SINGLE HEAD ADJUSTABLE 100 psi (6.9 bar)

	Model	Item Number Prefix	Pump Tube Number	Gallons per Day	Liters per Day
45 SERIES	45MHP2	45MJH1	#1	0.2-3.0	0.8-11.4
	45MHP10	45MJH2	#2	0.5-10.0	1.9-37.9
	45MHP22	45MJH7	#7	1.1-22.0	4.2-83.3
85 SERIES	85MHP5	85MJH1	#1	0.3-5.0	1.1-18.9
	85MHP17	85MJH2	#2	0.8-17.0	3.0-64.4
	85MHP40	85MJH7	#7	2.0-40.0	7.6-151.4

#### Voltage & Hertz

- A** 120V 60Hz
- B** 220V 60Hz
- C** 230V 50Hz, CEE7 Cord INTERNATIONAL
- D** 250V 50Hz, CEE7 Cord INTERNATIONAL

**NOTE:** Contact the factory for additional voltage and cord options.

#### Suction & Discharge Tubing

- 1** 1/4" White
- 2** 1/4" UV Black
- 3** 3/8" White
- 4** 3/8" UV Black
- 5** 6 mm White EUROPE

**NOTE:** O.D. does not affect output.

#### Tube Material

- S** Santoprene®
- T** Versilon™ (#7 not available)

**NOTE:** Application specific, refer to chemical resistance guide for chemical compatibility.

NOTE: Approximate Output @ 60Hz.

NOTE: Injection check valve included with pumps rated 26-100 psi (1.8-6.9 bar).

**NOTICE:** The information within this chart is solely intended for use as a guide. The output data is an approximation based on pumping water under a controlled testing environment. Many variables can affect the output of the pump. Stenner Pump Company recommends that all metering pumps undergo field calibration by means of analytical testing to confirm their outputs.

Order at [ChemWorld.com](http://ChemWorld.com) or call 800-658-7716.



# Classic 45 & 85 Single Head Stenner Pumps

## Fixed Output

### BUILD AN ITEM NUMBER FOR PUMP OR TANK SYSTEM



Select **Item Number Prefix** from output chart

#### SINGLE HEAD FIXED 25 psi (1.7 bar)

	Model	Item Number Prefix	Pump Tube Number	Gallons per Day	Liters per Day
45 SERIES	45MP1	45MFL1	#1	3.0	11.4
	45MP2	45MFL2	#2	10.0	37.9
	45MP3	45MFL3	#3	22.0	83.3
	45MP4	45MFL4	#4	35.0	132.5
	45MP5	45MFL5	#5	50.0	189.3
85 SERIES	85MP1	85MFL1	#1	5.0	18.9
	85MP2	85MFL2	#2	17.0	64.4
	85MP3	85MFL3	#3	40.0	151.4
	85MP4	85MFL4	#4	60.0	227.1
	85MP5	85MFL5	#5	85.0	321.8

#### Voltage & Hertz

- A** 120V 60Hz
- B** 220V 60Hz
- C** 230V 50Hz, CEE7 Cord INTERNATIONAL
- D** 250V 50Hz, CEE7 Cord INTERNATIONAL

**NOTE:** Contact the factory for additional voltage and cord options.

#### Suction & Discharge Tubing

- 1** 1/4" White
- 2** 1/4" UV Black
- 3** 3/8" White
- 4** 3/8" UV Black
- 5** 6 mm White EUROPE

**NOTE:** O.D. does not affect output.

#### SINGLE HEAD FIXED 100 psi (6.9 bar)

	Model	Item Number Prefix	Pump Tube Number	Gallons per Day	Liters per Day
45 SERIES	45MPHP2	45MFH1	#1	3.0	11.4
	45MPHP10	45MFH2	#2	10.0	37.9
	45MPHP22	45MFH7	#7	22.0	83.3
85 SERIES	85MPHP5	85MFH1	#1	5.0	18.9
	85MPHP17	85MFH2	#2	17.0	64.4
	85MPHP40	85MFH7	#7	40.0	151.4

#### Tube Material

- S** Santoprene®
- T** Versilon™ (#7 not available)

**NOTE:** Application specific, refer to chemical resistance guide for chemical compatibility.

NOTE: Approximate Output @ 60Hz.

NOTE: Injection check valve included with pumps rated 26-100 psi (1.8-6.9 bar).

**NOTICE:** The information within this chart is solely intended for use as a guide. The output data is an approximation based on pumping water under a controlled testing environment. Many variables can affect the output of the pump. Stenner Pump Company recommends that all metering pumps undergo field calibration by means of analytical testing to confirm their outputs.

Order at [ChemWorld.com](http://ChemWorld.com) or call 800-658-7716.