



**ChemWorld.com**

Worldwide Online Ordering and Consulting

(800) 658-7716

**ATLANTA WAREHOUSE**

3939 Royal Drive, Ste 224 and 226  
Kennesaw, GA 30144

**UTAH WAREHOUSE**

647 West Billinis Road, Unit 1  
Salt Lake City, Utah 84119

## **Chemworld 2338 / 2338D COOLING WATER TREATMENT FOR CLOSED SYSTEMS**

### **DESCRIPTION**

CHEMWORLD 2338 / 2338D is a closed water system treatment program in liquid form. The product contains a combination of nitrite, borate, and silicate formulated to minimize corrosion and deposition. CHEMWORLD 2338 / 2338D used in both hot and cold water systems. It is compatible with glycol heat transfer fluids. 2338D contains a "P" Indicator for ease of product detection or for monitoring water loss.

### **FEATURES AND BENEFITS**

- Controls corrosion
- Extends equipment life
- Improves overall equipment efficiency
- Protects multiple metallurgies

### **PRODUCT FEED AND CONTROL**

CHEMWORLD 2338 / 2338D is normally shot fed. The product is normally fed neat directly from the shipping container. Feeders, piping and valves should be made of steel, polyethylene, or PVC.

Treatment control ranges vary depending on system operating conditions. CHEMWORLD 2338 / 2338D is controlled by a nitrite test or nitrite strips.

### **PHYSICAL PROPERTIES**

Physical properties of CHEMWORLD 2338 / 2338D are shown on the Safety Data Sheet (SDS), a copy of which is available upon request.

### **STORAGE AND HANDLING**

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

### **ENVIRONMENTAL, HEALTH, AND SAFETY**

For detailed information, consult the safety data sheet (SDS).

### **PACKAGING**

CHEMWORLD 2338 / 2338D is available in a wide variety of customized containers and delivery methods.